



COOKTOP FEATURES

Total Burners	4 Italian Aluminum Burners
Front Left	15,000 BTU
Rear Left	9,000 BTU
Front Right	15,000 BTU
Rear Right	9,000 BTU

OVEN FEATURES

Oven Cavity	1
Oven Capacity	4.2 cu. ft.
Bake Element	2800W
Broil Element	3200W
Oven Modes	Broil, Bake, Convection Bake Convection Broil
Cleaning System	SteamClean
Oven Temp Range (F)	150° - 500 °

PRODUCT FEATURES

- **Black Enamel Cooktop:** Durable, easy-to-clean surface for everyday use.
- **Exclusive Continuous Cast Iron Grates:** Smooth pan movement across the cooktop without lifting.
- **Exclusive Zinc Alloy Knobs with Blue Cascade Lighting:** Elegant controls with illuminated accents for a premium look.
- **Single-Spark Ignition with Auto-Reignition:** Reliable ignition system for hassle-free cooking.
- **Italian Aluminum Burners:** Precision burners delivering consistent heat and performance.
- **Exclusive Knurled Stainless-Steel Handle:** Sturdy and stylish design for a comfortable grip.
- **SoftClose Oven Door with Removable Triple-Pane Glass:** Smooth, quiet closing with heat-resistant safety.
- **Single Convection Fan:** Even heat distribution for consistent baking and roasting.
- **Blue Enamel Oven Interior:** Durable, easy-to-maintain finish that withstands high temperatures.
- **Five Rack Positions:** Flexible cooking options for dishes of all sizes.
- **Included Accessories:** Telescopic guides with 2 racks and 1 enamel broiler pan for versatile cooking.

SAFETY FEATURES

- Appliance gas safety device
- Cooktop auto-reignition system
- Child safety lock
- Appliance anti-tip bracket

#### PRODUCT FEATURES

- Model No.: **VRN3009**
- Product Dimensions: **30"W × 27.375"D × 36"H**
- Package Dimensions: **36.3"W × 32.2"D × 45.6"H**
- Product Weight: **229 lbs**
- Electrical Supply: **240V / 60Hz**
- Electrical Service: **15-amp dedicated circuit**
- Gas Supply: **NG (Natural Gas) / LP conversion kit included**
- Plug: **Molded electrical plug, Type B (NEMA 14-50)**
- Distance to Vent Hood: **30" min / 36" max**
- Gas Connection: **½" gas fitting (bottom right)**



#### DIMENSIONS & CLEARANCES

Before installing the range, you must locate and secure the included anti-tip bracket to the wall for your range.

The range may be installed flush to the rear wall. You may install a non-combustible material on the rear wall above the range and up to the vent hood. It is not necessary to install non-combustible materials behind the range below the countertop height.

The minimum distance from the side of the range above the countertop to combustible sidewalls must be at least 10 inches.

